



US009282775B2

(12) **United States Patent**
Vorhies et al.

(10) **Patent No.:** **US 9,282,775 B2**
(45) **Date of Patent:** **Mar. 15, 2016**

(54) **SWITCH MECHANISMS FOR WEARABLE ARTICLES**

(71) Applicant: **Zackees, Inc.**, San Francisco, CA (US)

(72) Inventors: **Zachary James Vorhies**, San Francisco, CA (US); **Murat Ozkan**, San Francisco, CA (US); **Roger Fred Challender**, San Francisco, CA (US)

(73) Assignee: **Zackees, Inc.**, San Francisco, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **14/616,695**

(22) Filed: **Feb. 7, 2015**

(65) **Prior Publication Data**

US 2015/0150321 A1 Jun. 4, 2015

Related U.S. Application Data

(62) Division of application No. 14/023,459, filed on Sep. 10, 2013, now Pat. No. 9,013,281.

(51) **Int. Cl.**

B60Q 1/34 (2006.01)
A41D 19/00 (2006.01)
G08B 5/00 (2006.01)
B62J 6/00 (2006.01)
B60Q 1/26 (2006.01)
A41D 19/015 (2006.01)
A41D 13/01 (2006.01)

(52) **U.S. Cl.**

CPC **A41D 19/0031** (2013.01); **A41D 19/0024** (2013.01); **B60Q 1/2673** (2013.01); **B62J 6/005** (2013.01); **G08B 5/006** (2013.01); **A41D 13/01** (2013.01); **A41D 19/0157** (2013.01); **B62J 2300/008** (2013.01)

(58) **Field of Classification Search**

CPC G08B 5/006; A41D 13/01; A41D 19/0157

USPC 340/475, 12.5, 326

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,635,516 A * 1/1987 Giannini G10H 1/32
2/160
5,708,239 A * 1/1998 Konda H01H 1/38
200/1 R
6,529,121 B2 * 3/2003 Bush A41D 19/0157
340/321
6,592,235 B1 * 7/2003 Mayo A41D 19/0157
2/160
2004/0255361 A1 * 12/2004 Senter A41D 19/0157
2/160
2011/0078842 A1 * 4/2011 Tang A41D 19/0157
2/160

* cited by examiner


Primary Examiner — Tai T Nguyen

(74) *Attorney, Agent, or Firm* — Robert Moll

(57) **ABSTRACT**

This invention relates to electronic wearable articles such as clothing. The invention is an integrated wearable article (e.g. an electronic glove) that allows a user to signal to others the user intent for direction. The electronic glove includes a glove, a chevron-shaped light integrated with the glove that points away from the user when glove is on the hand of the user to indicate intended direction, and an electronic circuit including a switch mechanism with a first contact assembly on the thumb and a second contact assembly on the index finger of the glove, wherein the electronic circuit detects when the first contact assembly touches the second contact assembly to actuate the light, and a battery to power the electronic circuit.

2 Claims, 6 Drawing Sheets






Figure 1B




Figure 1A




Figure 2B




Figure 2A




Figure 3




Figure 4A





Figure 4B






Figure 6B




Figure 6A

1

SWITCH MECHANISMS FOR WEARABLE ARTICLES

This is a divisional application of U.S. application Ser. No. 14/023,459, Wearable Electronic Signaling Device, filed on Sep. 10, 2013, now U.S. Pat. No. 9,013,281, which is incorporated by reference herein.

BACKGROUND

This invention relates to electronic wearable articles. A significant reason people do not ride their bikes more often, particularly in urban areas with heavy traffic, is the fear of death or bodily harm from vehicle collisions. Because cyclists and vehicles share the road, it is important for drivers to understand where the cyclist is heading next. When a cyclist is turning left or right, he or she can indicate this by hand signals. However, not all drivers may recall the hand signaling rules and thus may not understand the rider's intent. Hand signals also suffer because they do not grab attention and from the fact they are not visible at night. Of course, this problem of signaling exists for skateboarders, runners, and roller skaters as well. There exists a need to quickly and clearly signal to vehicles that share the road with users (e.g., riders and runners) intent for direction.

SUMMARY OF THE INVENTION

This invention relates to electronic wearable articles. In a feature, the invention is integrated with an electronic wearable article, e.g. a glove or set of gloves, that allows a user to signal to others the user's intent for direction. In one aspect, the electronic glove includes a glove, a chevron-shaped light integrated with the glove that points away from the user when the glove is on the hand of the user to indicate intended direction, and an electronic circuit including a switch mechanism with a first contact assembly on the thumb and a second contact assembly on the index finger of the glove, wherein the electronic circuit detects when the first contact assembly touches the second contact assembly to actuate the light, and a battery to power the electronic circuit.

In a feature of the invention, the switch mechanism includes a first contact assembly including a first conductive plate with a first shaft, a first ring terminal disposed on the first shaft, a first stranded wire connected to the first ring terminal, a second conductive plate with a first hole mated with the first shaft, wherein the first ring terminal contacts either the first conductive plate or the second conductive plate or both of the first and second conductive plates, a second contact assembly including a third conductive plate with a second shaft, a second ring terminal disposed on the second shaft, a second stranded wire connected to the second ring terminal, and a fourth conductive plate with a second hole mated with the second shaft, wherein the second ring terminal contacts either the third conductive plate or the fourth conductive plate or both of the third and fourth conductive plates, wherein the first and the second contact assemblies make contact to actuate the switch mechanism.

In a feature of the invention, the contact assembly includes a first conductive plate with a shaft, a ring terminal disposed on the shaft, a stranded wire connected to the ring terminal, and a second conductive plate with a hole mated with the shaft, wherein the ring terminal contacts either the first conductive plate or the second conductive plate or both of the first and second conductive plates.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1A is a perspective view of a left-handed electronic glove.

2

FIG. 1B is a perspective view of a right-handed electronic glove.

FIG. 2A illustrates the right-handed electronic glove of FIG. 1B with the chevron-shaped light **104** signaling persons in front of the user.

FIG. 2B illustrates the right-handed electronic glove of FIG. 1B with the chevron shaped light **104** signaling persons in back of the user.

FIG. 3 is a schematic of an embodiment of the electronic circuit suitable for use in the electronic glove.

FIG. 4A is an exploded view of the contact assembly and a portion of the electronic wearable article.

FIG. 4B is a view of the contact assembly integrated with the electronic wearable article.

FIG. 5A is a top view of the switch mechanism exposed in the electronic wearable article.

FIG. 5B is a cross-sectional view through line 5B-5B of the switch mechanism in FIG. 5A.

FIG. 6A illustrates the left-handed electronic glove with a cutaway to show the switch mechanism coupled with stranded wires to the electronic circuit and a chevron-shaped light.

FIG. 6B illustrates the right-handed electronic glove with a cutaway to show the switch mechanism coupled with stranded wires to the electronic circuit and a chevron-shaped light.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

The following description includes the best mode of carrying out the invention, illustrates the principles of the invention, uses illustrative values, and should not be taken in a limiting sense. The scope of the invention is determined by reference to the claims. Each part or step is assigned its own number in the specification and drawings. The drawings are not to scale and do not reflect the relative size.

FIG. 1A is a perspective view of an embodiment of a left-handed electronic glove. As shown in FIG. 1A, electronic glove **101** includes a chevron-shaped light **106** activated by switch mechanism **102** integrated with the electronic glove **101** so that the chevron-shaped light **106** points away from the user when electronic glove **101** is on the hand to indicate the intended direction. Similarly, FIG. 1B includes chevron-shaped light **104**, switch mechanism **103** integrated in the right-handed electronic glove **105**.

FIG. 2A illustrates the right-handed electronic glove of FIG. 1B with the chevron-shaped light **104** signaling persons in front of the user.

FIG. 2B illustrates the right-handed electronic glove of FIG. 1B with the chevron-shaped light **104** to signal persons in back of the user.

The chevron-shaped light **106** of the left-handed glove **101** can be used in similar fashion.

FIG. 3 is a schematic of an embodiment of the electronic circuit for use in the electronic gloves **101**, **105**. The electronic circuit **300** includes a battery **302** which provides a power supply rail **304** and a ground reference **326** for the electronic circuit **300**. The behavior of the electronic circuit **300** is driven by the microcontroller unit (MCU) **316** which contains in one IC package, a central processor unit, non-volatile program memory, volatile memory for data, and a range of I/O peripherals to interact with external system components (not shown). A suitable MCU is part number PIC12LF1840 from Microchip Technology Inc. in Chandler, Ariz. When using part number PIC12LF1840 as the MCU **316**, we connect a digital input capable pin of the MCU **316** to

3

the switch mechanism **102** consisting of two contact assemblies **400**, **500** that form the two contacts of the switch mechanism **102**. The contact assembly **400** connected to the input pin of the MCU **316** is pulled up to the power supply rail **304** through a resistor **312** suitably sized (e.g., 10 k ohms) to allow the voltage level to drop below the logic low threshold (V_{IL}) of the MCU input pin when the switch mechanism **102** is closed.

The ambient light sensor (ALS) **314** includes a transducer in an IC package and supporting circuitry to convert light incident on the transducer's IC package into an electrical signal capable of being read by the MCU **316**. One suitable ALS is part number SFH 5711 manufactured by Osram GmbH in Munich, Germany. In an embodiment of the electronic circuit **300**, the ALS **314** is routed to a pin (not shown) of the MCU **316** that is capable of being an input to the analog-to-digital converter (not shown) of the MCU **316**. In this embodiment, the light assembly **328** that constitutes the illuminated chevron light includes light emitting diodes such as LED **310** with a current limiting resistor **320**.

In an embodiment, the light assembly **328** is a variable number of parallel-connected light emitting diodes **310** and current limiting resistors **320**. A suitable LED is part number APTD3216SYCK from Kingbright Inc. in City of Industry, Calif. A suitable current limiting resistor **320** is 49.9 ohms. In an embodiment, a lithium coin cell battery powers eleven light emitting diodes **310**. The driver circuit **318** for the light assembly **328** is an electronically controllable switch capable of passing the current demanded by the light assembly **328** such as an N-channel MOSFET with its gate connected to an output-capable I/O pin of the MCU **316**. A suitable N-channel MOSFET is part number DMG1013UW-7 manufactured by Diodes Inc in Plano, Tex.

FIG. 3 illustrates the electronic circuit **300** can be implemented for mechanical flexibility of the wearable article on two printed circuit boards as indicated to the left and right side of the dotted line **306**.

FIG. 4A is an exploded view of the contact assembly and a portion of the electronic wearable article (e.g., glove). As shown, the contact assembly **400**, includes a third conductive plate **402** with a shaft **403** inserted in a second ring terminal **406** and a hole **408** in a portion **410** of the electronic wearable article, a stranded wire **401** connected to the second ring terminal **406**, and a fourth conductive plate **412** with a hole **411** to mate with the shaft **403**.

The stranded wire **401** is defined as a collection of electrically conductive wires, made of copper or tinned copper, where each individual strand measuring 0.3 mm or less in diameter, is bundled together to form a larger wire. This bundle of wire can be straight, parallel, twisted or braided strands.

In other embodiments, the stranded wire can be made of copper, silver, tin, gold, aluminum, nickel or a combination of those as coatings or mixed together alloys. The wire bundled is sheathed in an electrical insulation comprising of Silicon, polyvinyl chloride, polytetrafluoroethylene or equivalent.

FIG. 4B is a view of the fully assembled contact assembly integrated with the electronic wearable article. In an embodiment, we strip the insulation from the end of stranded wire **401** at exposed portion **404**, bend the wire strands back over the insulated part of the stranded wire **401** and this is inserted into a barrel **405** of the second ring terminal **406** to ensure good electrical contact between the exposed portion **404** of the stranded wire **401** and the second ring terminal **406**. In an embodiment, the bent back portion of the exposed portion **404** of the stranded wire is disposed in the barrel **405** of the second ring terminal **406**. The barrel **405** is crimped down to

4

secure the stranded wire **401** to the second ring terminal **406**. In another embodiment, conductive adhesive (e.g. epoxy) or solder is used to secure the stranded wire **401** to the second ring terminal **406**.

When assembled, the second ring terminal **406** contacts either the third conductive plate **402** or the fourth conductive plate **412** or both of the conductive plates **402** and **412**. Further, the stranded wire **401**, the second ring terminal **406**, and the third conductive plate **402** are on the inside of the electronic wearable article, leaving only the top conductive plate exposed to view.

FIG. 5A is a top view of the exposed part of the switch mechanism that is integrated in the electronic wearable article. It also indicates a cross-section through line 5B-5B.

FIG. 5B is the cross-sectional view through a line 5B-5B of an embodiment of the switch mechanism. The switch mechanism **102** includes a first contact assembly **500** and a second contact assembly **400**.

The first contact assembly **500** includes a first conductive plate **502** with a first shaft **504**, a first ring terminal **501** disposed on the first shaft **504**, an exposed portion **510** of a first stranded wire **508** inside the barrel **506** of the first ring terminal **501**, a second conductive plate **511** with a first hole (not shown) mated with the first shaft **504**, wherein the first ring terminal **501** contacts the first conductive plate **502** or the second conductive plate **511** or both of the conductive plates **502**, **511**. As shown, the first shaft **504** extends through a hole in a portion **512** of the electronic wearable article.

The second contact assembly **400** includes a third conductive plate **402** with a second shaft **403**, a second ring terminal **406** disposed on the second shaft **403**, a second stranded wire **401** with an exposed portion **404** of second stranded wire **401** inside the barrel **405** of the second ring terminal **406**, a fourth conductive plate **412** with a second hole **411** mated with the second shaft **403**, wherein the second ring terminal **406** contacts either the third conductive plate **402** or the fourth conductive plate **412** or both of the conductive plates **402**, **412**, wherein the first and the second contact assemblies **400**, **500**, make physical contact to actuate the switch mechanism **102**.

FIG. 6A illustrates the left-handed electronic glove **101** with a cutaway to show the switch mechanism **102** of the contact assemblies **400**, **500** coupled by the stranded wires **401**, **407** to the electronic circuit PCB1 and an illuminated light surface **600** that define the chevron-shaped light.

FIG. 6B illustrates the right-handed electronic glove **105** with a cutaway to show the switch mechanism **103**, which has the same construction as switch mechanism **102** of contact assemblies **415**, **417**, which has the same construction as contact assemblies **400**, **500** coupled by the stranded wires **409**, **413** to the electronic circuit PCB2 and an array of discrete point sources of light **328** that define the chevron-shaped light.

We claim:

1. A switch mechanism for a wearable article, comprising:
 - a first contact assembly including:
 - a first conductive plate with a first shaft;
 - a first ring terminal disposed on the first shaft;
 - a first stranded wire connected to the first ring terminal;
 - a second conductive plate with a first hole mated with the first shaft, wherein the first ring terminal contacts either the first conductive plate or the second conductive plate or both of the first and second conductive plates;
 - a second contact assembly including:
 - a third conductive plate with a second shaft;
 - a second ring terminal disposed on the second shaft;
 - a second stranded wire connected to the second ring terminal; and

5**6**

a fourth conductive plate with a second hole mated with the second shaft, wherein the second ring terminal contacts either the third conductive plate or the fourth conductive plate or both of the third and fourth conductive plates, wherein the first and the second contact assemblies are adapted to secure to the wearable article and make contact to actuate the switch mechanism. 5

2. The switch mechanism of claim 1, wherein a convex curve of the first conductive plate faces a convex curve of the second conductive plate. 10

* * * * *